

IN THE CLAIMS:

1. (Currently Amended) In a Home Network telephone system, a method for controlling communications privacy, the method comprising:

transceiving calls on at least one external telephone line communicating information in a first format;

~~at a gateway, converting between the first format and a digital Home Network format; and,~~

supplying privacy and public mode bridging options;

independently selecting private and public modes for each external telephone line;

in response to the selecting the public mode for a first external telephone line, permitting bridges through a gateway, between the first external telephone line and any endpoint; and,

in response to selecting the privacy mode for the first external telephone line, selectively excluding bridges through the gateway, between the first external telephone line[[s]] and a plurality of Home Network the endpoints.

2. (Currently Amended) The method of claim 1 wherein selectively excluding bridges between the first external telephone line[s] and ~~a plurality of Home Network the endpoints~~ includes exclusively bridging a call between [[a]] the first external telephone line and a first endpoint ~~from among the plurality of endpoints.~~

3. Canceled

4. (Currently Amended) The method of claim ~~[[3]]~~ 1 wherein permitting bridges between the first external telephone line and any other endpoints in the system includes:

from a second endpoint, selecting the first external telephone line; and,

while the call is bridged to the first endpoint, adding a bridge between the first telephone line and the second endpoint.

5. (Currently Amended) The method of claim ~~[[3]]~~ 1 wherein selecting the public mode for the first external telephone line selectively excluding bridges between external telephone lines and a plurality of Home Network endpoints includes:

while in the public mode, bridging a call between the first telephone line and the first endpoint; and,

adding a bridge between the first external telephone line and a second endpoint; and,

the method further comprising:

toggling to the privacy mode for the first external telephone line; and,

in response to toggling to the privacy mode, dropping the bridge between the first telephone line and the second endpoint.

6. (Currently Amended) The method of claim ~~[[3]]~~ 1 wherein selecting the public mode for the first external telephone line selectively excluding bridges between external telephone lines and a plurality of Home Network endpoints includes, while in the public mode,

bridging a call between the first telephone line, the first endpoint, and a second endpoint; and,

the method further comprising:

selecting the privacy mode for the first external telephone line; and,

in response to selecting the privacy mode, preventing a bridge between the first telephone line and other endpoints in the system.

7. (Currently Amended) The method of claim 1 further comprising:

wherein selecting the privacy mode for the first external telephone line;

~~wherein selectively excluding bridges between external telephone lines and a plurality of Home Network endpoints~~ includes:

bridging a call between ~~[[a]]~~ the first external telephone line and a first endpoint; and,

in response to selecting the privacy mode for the first external telephone line, preventing bridges between the first external telephone line and other endpoints in the system.

8. (Currently Amended) The method of claim 7. wherein selecting the privacy mode for the first external telephone line ~~selectively excluding bridges between external telephone lines and a plurality of Home Network endpoints~~ includes, while in the privacy mode, bridging a call between the first telephone line and the first endpoint; and,

the method further comprising:

to toggling to the public mode for the first external telephone line; and,

in response to toggling to the public mode, adding a bridge between the first telephone line and a second endpoint.

9. (Original) The method of claim 7 wherein preventing a bridge between the first telephone line and other endpoints in the system includes:

from a second endpoint, selecting the first external telephone line; and,

while the call is bridged between the first telephone line and the first endpoint, preventing a bridge between the first telephone line and the second endpoint.

10. (Currently Amended) The method of claim 1 wherein transceiving calls on at least one external telephone line includes communicating information in a first format:

the method further comprising:

at a gateway, converting between the first format and a digital Home Network format;

establishing traffic channels between the gateway and the endpoints to communicate information in the Home Network format; and, establishing control channels to control endpoint privacy.

11. (Original) The method of claim 10 wherein establishing a control channel to control endpoint privacy includes:

using the control channels to communicate privacy and public mode selections to the gateway from the endpoints; and,
using the control channels to send mode selection acknowledgements from the gateway to communicating endpoints, in response to making the privacy and public mode selections.

12. Canceled

13. (Currently Amended) The method of claim [[12]]
11 further comprising:

at the gateway, establishing a default mode flag for the [[a]]
first external telephone line node;

wherein using the control channels to communicate privacy and public mode selections from the endpoints to the gateway includes using the control channels to select default mode flags; and,

wherein selectively excluding bridges between the first
external telephone line[[s]] and ~~a plurality of Home Network~~ the
endpoints includes using the default mode flags to determine whether a privacy or a public mode has been selected for the first external telephone line node.

14. (Currently Amended) The method of claim 13
further comprising:

at the gateway, establishing a permission flag for each
external telephone line node;

wherein using the control channels to communicate privacy and public mode selections from the endpoints to the gateway includes:

using the control channels to select default mode flags;
checking the permission flag status to determine if the
communicating node has permission to change default mode flags; and,
wherein selectively excluding bridges between the first
external telephone line[[s]] and ~~a plurality of Home Network~~ the
endpoints includes changing the default mode flag in response to the
permission flag status.

15. (Currently Amended) The method of claim 13
further comprising:

at the gateway establishing a toggle flag for each default
mode flag;

wherein using the control channels to communicate privacy
and public mode selections from the endpoints to the gateway includes:

using the control channels to select toggle flags for a first call
bridged to the first external telephone line node selected from the group
including on-going and subsequent calls; and,

wherein selectively excluding bridges between the first
external telephone line[[s]] and ~~a plurality of Home Network~~ the
endpoints includes using the toggle flag to change the default mode flag
for the first call involving the first external telephone line node.

16. (Currently Amended) The method of claim 15
further comprising:

in response to preventing a bridge between the first external
telephone line and the a second endpoint, sending a communication from
the gateway to the second endpoint selected from the group including a

busy signal and a message indicating that a privacy mode call is currently in progress.

17. (Currently Amended) The method of claim 15 further comprising:

in response to preventing a bridge between the first external telephone line and the a second endpoint, bridging the second endpoint to an unused external telephone line.

18. (Original) The method of claim 15 further comprising:

following the bridging of a call between the first external telephone line and the first endpoint in the privacy mode, using the control channels to send a transfer command; and,

while the call is in progress, terminating the bridge between the first external telephone line and the first endpoint, and establishing a bridge between the first external telephone line and the second endpoint.

19. (Currently Amended) The method of claim 15 wherein selectively excluding bridges between the first external telephone line[[s]] and a plurality of Home Network the endpoints includes bridging a call in response to receiving the call on an external telephone line.

20. (Currently Amended) The method of claim 15 wherein selectively excluding bridges between the first external telephone line[[s]] and a plurality of Home Network the endpoints includes originating the call from an endpoint.

21. (Original) The method of claim 20 wherein originating the call from an endpoint includes selecting an external telephone line from the endpoint.

22. (Original) The method of claim 15 further comprising:

using an input/output (I/O) device, supplying privacy and public default mode selections, permission flag selections, and toggle flag selections to the gateway.

23. (Previously Amended) A Home Network telephone privacy management system comprising:

a gateway having a port for transceiving calls on at least one external telephone line ~~in a first format, the gateway converting between the first format and a digital Home Network format, and the gateway having~~ a port for receiving public and privacy mode selection commands, independently for each external telephone line, and a port for selectively establishing bridges to the external telephone lines ~~in response to privacy and public modes; and,~~

a plurality of Home Network endpoints, each endpoint having a user interface to accept mode commands and external telephone line selection commands, each endpoint having a port connected to the gateway for supplying mode and external telephone line selection commands, each endpoint having a port for establishing bridges to external telephone lines through the gateway;

wherein the gateway, in response to the selection of the public mode for a first external telephone line, permits bridges between the first external telephone line and any endpoint; and

wherein the gateway, in response to the selection of the privacy mode for the first external telephone line, selectively excludes bridges between the first external telephone line and the endpoints.

24. (Currently Amended) The system of claim 23 wherein the gateway exclusively bridges a call between ~~[[a]]~~ the first external telephone line and a first endpoint in the privacy mode.

25. (Currently Amended) The system of claim 23 wherein the gateway bridges a call between ~~[[a]]~~ the first external line, a first endpoint, and a second endpoint in the public mode.

26. (Currently Amended) The system of claim 23 wherein the gateway bridges a call between ~~[[a]]~~ the first external telephone line and a first endpoint, and prevents bridges between the first external telephone line and other endpoints in the system in the privacy mode.

27. (Original) The system of claim 26 wherein the gateway bridges a call between the first external telephone line and the first endpoint in the privacy mode; and,

wherein the gateway permits bridges between the first external telephone line and other endpoints in the system, in response to receiving a public mode toggle command.

28. (Original) The system of claim 26 wherein the gateway bridges a call between the first external telephone line and the first endpoint in the public mode; and,

wherein the gateway adds a bridge between the first telephone line and a second endpoint while the call is bridged to the first endpoint.

29. (Original) The system of claim 23 wherein the gateway bridges a call between a first telephone line and a first endpoint, and adds a bridge between the first external telephone line and a second endpoint; and,

wherein the gateway drops the bridge between the first telephone line and the second endpoint in response to a privacy mode toggle command.

30. (Currently Amended) The system of claim 23 wherein the gateway bridges a call between [[a]] the first telephone line, a first endpoint, and a second endpoint in the public mode; and,

wherein the gateway prevents a bridge between the first telephone line and other endpoints in the system in response to a privacy mode toggle command.

31. (Currently Amended) The system of claim 23 wherein the gateway bridges a call between [[a]] the first external telephone line and a first endpoint in the privacy mode;

wherein a second endpoint selects the first external telephone line while the call is bridged between the first telephone line and the first endpoint; and,

wherein the gateway prevents a bridge between the first telephone line and the second endpoint.

32. (Currently Amended) The system of claim 23 wherein the gateway transceives calls on the external telephone lines in a first format, converts between the first format and a digital Home Network format, establishes traffic channels between the gateway and the endpoints to communicate information in the Home Network format, and establishes control channels to manage endpoint privacy.

33. (Original) The system of claim 32 wherein the plurality of endpoints use the control channels to communicate privacy and public mode commands to the gateway; and,

wherein the gateway uses the control channels to send mode selection acknowledgements to the endpoints.

34. Canceled

35. (Currently Amended) The system of claim ~~[[34]]~~ 33 wherein the gateway receives a privacy mode command for ~~[[a]]~~ the first external telephone line and exclusively bridges a call to an endpoint originating a call through the first external telephone line.

36. (Currently Amended) The system of claim ~~[[34]]~~ 33 wherein the gateway receives a privacy mode command for ~~[[a]]~~ the first external telephone line and exclusively bridges a call to an endpoint receiving a call through the first external telephone line.

37-38. Canceled

39. (Currently Amended) The system of claim 33 wherein a first endpoint selects the privacy mode for the first external telephone line;

wherein the gateway bridges a call between ~~[[a]]~~ the first external telephone line and the first endpoint;

wherein a second endpoint selects the first external telephone line while the call is bridged between the first telephone line and the first endpoint; and,

wherein the gateway sends a communication to the second endpoint selected from the group including a busy signal and a message indicating that a privacy mode call is currently in progress.

40. (Currently Amended) The system of claim 33 wherein a first endpoint selects the privacy mode for the first external telephone line;

wherein the gateway bridges a call between ~~[[a]]~~ the first external telephone line and the first endpoint;

wherein a second endpoint selects the first external telephone line while the call is bridged between the first telephone line and the first endpoint; and,

wherein the gateway bridges the second endpoint to an unused external telephone line.

41. (Currently Amended) The system of claim ~~[[34]]~~ 33 wherein a first endpoint supplies a transfer command to the gateway for the transfer of a privacy mode call to a second endpoint; and, wherein the gateway, while the call is in progress, terminates the bridge between ~~[[a]]~~ the first external telephone line and the first endpoint, and establishes a bridge between the first external telephone line and the second endpoint in response to the transfer command.

42. (Currently Amended) The system of claim ~~[[34]]~~ 33 wherein the system further comprises a gateway flag repository having a default mode flag for each corresponding external telephone line node, wherein the flag repository has a port to accept control channel communications for selecting default mode flags and for communications with the gateway; and,

wherein the gateway accesses default mode flags in the flag repository to determine whether a privacy or a public mode has been selected for a corresponding external telephone line node.

43. (Original) The system of claim 42 wherein the flag repository further includes a permission flag corresponding to each endpoint; and,

wherein the gateway receives control channel communications from endpoints attempting to change the default mode

flag, the gateway checking the corresponding permission flag status to determine whether a communicating endpoint has permission to change the default mode status, and the gateway changing the default mode flags in response to the permission flag values.

44. (Original) The system of claim 43 wherein the flag repository includes toggle flags for each corresponding default mode flag; and,

wherein the gateway receives control channel communications for setting toggle flag values, the gateway checking the toggle values during a first call selected from the group including on-going and subsequent calls, and overriding the default mode flag for the first call in response to the toggle value.

45. (Original) The system of claim 44 further comprising:

an input/output (I/O) device having a user interface for accepting external telephone line privacy and public selection commands and a port connected to the gateway for selecting flag repository flag values.

46. (New) The method of claim 1 further comprising:
independently selecting private and public modes for each Home Network endpoint;

in response to the selecting the public mode for a first endpoint, permitting bridges through the gateway, between a second

endpoint and the first external telephone line, when the first endpoint is bridged to the first external telephone line; and,

in response to selecting the privacy mode for the first endpoint, excluding bridges through the gateway, between the second endpoint and the first external telephone line, when the first endpoint is bridged to the first external telephone line.

47. (New) The method of claim 46 wherein selecting the privacy mode for the first endpoint includes exclusively bridging a call to an external telephone line through which the first endpoint originates a call.

48. (New) The method of claim 46 wherein selecting the privacy mode for the first endpoint includes exclusively bridging a call to an external telephone line from which the first endpoint receives a call.

49. (New) The system of claim 23 wherein the gateway receives public and privacy mode selection commands, independently for endpoints;

wherein the gateway, in response to the selection of the public mode for a first endpoint, permits bridges between a second endpoint and the first external telephone line, when the first endpoint is bridged to the first external telephone line; and,

wherein the gateway, in response to selection of the privacy mode for the first endpoint, excludes bridges between the second endpoint and the first external telephone line, when the first endpoint is bridged to the first external telephone line.

50. (New) The system of claim 49 wherein the gateway exclusively bridges a call between the first endpoint and the first external telephone line when operating in the privacy mode.

51. (New) The system of claim 49 wherein the gateway bridges a call between the first endpoint and the first external telephone line, and prevents bridges between the first external telephone line and other endpoints when operating in the privacy mode.

52. (New) The system of claim 49 wherein the gateway transceives calls on the external telephone lines in a first format, converts between the first format and a digital Home Network format, establishes traffic channels between the gateway and the endpoints to communicate information in the Home Network format, and establishes control channels to manage endpoint privacy.

53. (New) The system of claim 49 wherein the gateway receives a privacy mode command for the first endpoint and exclusively bridges a call to an external telephone line through which the first endpoint originates a call.

54. (New) The system of claim 49 wherein the gateway receives a privacy mode command for the first endpoint and exclusively bridges a call to an external telephone line from which the first endpoint receives a call.